


# Table de conversion des fluides



Fluid	Property	Value	Fluid	Property	Value
R407C	[°C]	-60 to 80	R407C	[°C]	-60 to 80
	[°F]	-80 to 170		[°F]	-80 to 170
Dew	[°C]	-60 to 80	Dew	[°C]	-60 to 80
	[°F]	-80 to 170		[°F]	-80 to 170
R407C	[°C]	-60 to 80	R407C	[°C]	-60 to 80
	[°F]	-80 to 170		[°F]	-80 to 170
Bubble	[°C]	-60 to 80	Bubble	[°C]	-60 to 80
	[°F]	-80 to 170		[°F]	-80 to 170
R134a	[°C]	-60 to 80	R134a	[°C]	-60 to 80
	[°F]	-80 to 170		[°F]	-80 to 170
R717	[°C]	-60 to 80	R717	[°C]	-60 to 80
	[°F]	-80 to 170		[°F]	-80 to 170
Pabs[psia]	[psia]	0 to 200	Pabs[psia]	[psia]	0 to 200
	[in Hg]	0 to 30		[in Hg]	0 to 30
Pabs[bar]	[bar]	0 to 20	Pabs[bar]	[bar]	0 to 20
	[lbf/in²]	0 to 300		[lbf/in²]	0 to 300
Bubble point	[°C]	-60 to 80	Bubble point	[°C]	-60 to 80
	[°F]	-80 to 170		[°F]	-80 to 170
Dew point	[°C]	-60 to 80	Dew point	[°C]	-60 to 80
	[°F]	-80 to 170		[°F]	-80 to 170
Pabs[psia]	[psia]	0 to 200	Pabs[psia]	[psia]	0 to 200
	[in Hg]	0 to 30		[in Hg]	0 to 30
Pabs[bar]	[bar]	0 to 20	Pabs[bar]	[bar]	0 to 20
	[lbf/in²]	0 to 300		[lbf/in²]	0 to 300
R410A	[°C]	-70 to 65	R410A	[°C]	-70 to 65
	[°F]	-100 to 150		[°F]	-100 to 150
R507	[°C]	-70 to 70	R507	[°C]	-70 to 70
	[°F]	-100 to 160		[°F]	-100 to 160
R404A	[°C]	-70 to 90	R404A	[°C]	-70 to 90
	[°F]	-90 to 150		[°F]	-90 to 150
R22	[°C]	-70 to 90	R22	[°C]	-70 to 90
	[°F]	-90 to 150		[°F]	-90 to 150
Pabs[psia]	[psia]	0 to 600	Pabs[psia]	[psia]	0 to 600
	[in Hg]	0 to 80		[in Hg]	0 to 80
Pabs[bar]	[bar]	0 to 40	Pabs[bar]	[bar]	0 to 40
	[lbf/in²]	0 to 600		[lbf/in²]	0 to 600